

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Farm Duty Single-Phase
Product code : 14796859
Catalog # : 00158ES1RFD56H-S

Frame	: 56H	Locked rotor time	: 14s (cold) 8s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 15.0/7.48 A	Protection degree	: IP55
L. R. Amperes	: 120/59.8 A	Cooling method	: IC411 - TEFC
LRC	: 8.0x(Code L)	Mounting	: F-1
No load current	: 8.60/4.30 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1745 rpm	Noise level ²	: 54.0 dB(A)
Slip	: 3.06 %	Starting method	: Direct On Line
Rated torque	: 4.51 ft.lb	Approx. weight ³	: 43.0 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1426 sq.ft.lb		
Design	: L		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	69.0	75.0	77.0	Max. traction	: 95 lb
Power Factor	0.68	0.78	0.83	Max. compression	: 144 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6204 2RS	6202 2RS
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	01/07/2026			

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage




Customer :

Product line : Rolled Steel Farm Duty Single-Phase

Product code : 14796859

Catalog # : 00158ES1RFD56H-S



Performance : 115/230 V 60 Hz 4P

Rated current : 15.0/7.48 A
LRC : 8.0
Rated torque : 4.51 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 270 %
Rated speed : 1745 rpm

Moment of inertia (J) : 0.1426 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : L

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	01/07/2026				