

DATA SHEET

Premium Efficiency Motor: **ODP1.5-18-145T,**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 31-Mar-2025

Document ID:

Customer:

MOTOR INFORMATION

HP	1.5
RPM	1800
Phase	3
Frequency	60
Voltage	230/460
Frame Size	143/5T
Enclosure	ODP
Degree of Protection	IP23
Service Factor	1.15
Poles	4
Full Load Speed	1747
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	L
Duty Cycle	S1 / Continuous
Slip	2.96%
NEMA Design	B
Moment of Inertia	0.091 lb.ft.^2
Locked Rotor Time (Hot)	12 seconds
Sound Pressure Level	51 dB(A)
Number of Starts	2 Cold / 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Safe Area
Inverter Rating	10:1 CT / 20:1 VT
Standard	NEMA MG 1
Approvals	UL, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	86.5 %	0.76
75%	87.0 %	0.68
50%	85.1 %	0.55

TORQUE

FULL LOAD	LRT	BDT
4.44 lb.ft.	352 %	373 %

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	4.2A	2.1A
Locked Rotor Amps	34.52A	17.26A
No Load Current	2.44A	1.22A
Usable at 208V	4.64A	

BEARING INFORMATION

DE Bearing	6205ZZ
ODE Bearing	6204ZZ
Grease Type	NSK SN7
DE Regreasing Interval	-- Hours
ODE Regreasing Interval	-- Hours
Grease Quantity	--

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	AISI 1045
Connection Diagram	9 Lead Wye
Approximate Weight	34.2 lbs.


MOTOR DRAWING

Premium Efficiency Motor: **ODP1.5-18-145T**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	P	O	T	AB
E	2F1	2F2	H	BA									
2.75	4	5	0.34	2.25	6.5	6.5	11.974	3.5	0.118	6.5	6.73	--	5.384

SHAFT & KEY				
S	ES	R	N-W	U
0.188	1.41	0.771	2.25	0.875

T-BOX	GND LUG
AA	
1.09	M5*P0.8

PERFORMANCE CURVES

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

ODP1.5-18-145T


Document Generated: 31-Mar-2025

Document ID:


Customer:

Motor Type	ODP				
Output Rating (HP)	1.5		FL Speed	1747	
Full Load Torque	4.44 lb.ft		LRT (%FLT)	352	460 volt FLA 2.1
Rotor Wk^2	0.865 lb-ft^2		BDT (%FLT)	373	230 volt FLA 4.2

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE



NAMEPLATE / WIRING

Premium Efficiency Motor: **ODP1.5-18-145T**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 31-Mar-2025
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		CC306B		OPEN DRIP PROOF 3 PHASE MOTOR											
Model :		Encl : ODP		SN :								4 5 6			
HP :	Poles :	FR :	Ins : F	IP 23	Max Amb 40°C	Duty : Cont		7 8 9		1 2 3		L1 L2 L3			
Hz: 60	CODE:		Hz: 50		Design: B		DE BRG:		4 5 6		7 8 9		L1 L2 L3		
Volts: 230/460	P.F.:		Volts: 190/380		ODE BRG:		230 V		4 5 6		7 8 9		L1 L2 L3		
Amps:	Eff: %		Amps:		WT: LBS		460 V		4 5 6		7 8 9		L1 L2 L3		
RPM:	S.F.: 1.15		RPM:		Date:				4 5 6		7 8 9		L1 L2 L3		
WorldWide Electric Corporation															

Model: ODP1.5-18-145T		Encl: ODP					
HP: 1.5	Poles: 4	Frame 143/5T	Ins Cl: F	IP IP23			
Hz: 60	Code: L	Hz: 50	Design: B				
Volts: 230/460	P.F.: 0.76	Volts: 190/380	DE Brg: 6205ZZ				
Amps: 4.2/2.1	Eff: 86.5%	Amps: 4.8/2.4	ODE Brg: 6204ZZ				
RPM: 1747	S.F.: 1.15	RPM: 1450	WT: 34.2 lbs.				
		S.F.: 1.0					