

DATA SHEET

Premium Efficiency Motor: **PEWWE5-36-184T**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 8-Oct-2024

Document ID:

Customer:

MOTOR INFORMATION

HP	5
RPM	3600
Phase	3
Frequency	60 Hz
Voltage	230/460 V
Frame Size	184T
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.25
Poles	2
Full Load Speed	3490
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	J
Duty Cycle	S1 / Continuous
Slip	3.06%
NEMA Design	B
Moment of Inertia	0.16 lb.ft.^2
Locked Rotor Time (Hot)	12 seconds
Sound Pressure Level	64 dB(A)
Number of Starts	2 Cold/ 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Class 1 Division 2 Groups A,B,C,D T3C(160°C)
Inverter Rating	10:1 CT / 20:1 VT PWM Type
Standard	NEMA MG-1
Approvals	CSA-US, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	88.5 %	0.88
75%	89.8 %	0.83
50%	89.6 %	0.73

TORQUE

FULL LOAD	LRT	BDT
7.52 lb.ft.	210 %	340 %

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	12A	6.01A
Locked Rotor Amps	92A	46A
No Load Current	4.6A	2.3A
Usable at 208V	13.3A	

BEARING INFORMATION

DE Bearing	6206ZZ C3
ODE Bearing	6206ZZ C3
Grease Type	-
DE Regreasing Interval	- Hours
ODE Regreasing Interval	- Hours

ADDITIONAL DATA

F2 Suitable	Yes
Shaft Material	1045 Carbon Steel
Connection Diagram	230 / 460 V - 9 Lead Y
Approximate Weight	91 lbs.


MOTOR DRAWING

Premium Efficiency Motor: **PEWWE5-36-184T**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F	H	BA										
3.75	4.5	5.5	0.41	2.75	8.898	6.852	15.827	4.5	0.591	1.969	9.606	9.5	1.417	7.876

SHAFT & KEY				
S	ES	R	N-W	U
0.25	1.78	0.986	2.75	1.125

TERMINAL BOX				
AA	XB	XC	XD	XF
1	2.26	5.124	4.567	5.509

PERFORMANCE CURVES

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

PEWWE5-36-184T


Document Generated: 8-Oct-2024

Document ID:


Customer:

Motor Type	PEWWE		FL Speed	3490			
Output Rating (HP)	5		LRT (%FLT)	210	460 volt FLA	6.01	A
Full Load Torque	7.52	lb.ft	BDT (%FLT)	340	230 volt FLA	12	A
Rotor Wk^2	0.16	lb-ft^2					

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE



NAMEPLATE / WIRING

Premium Efficiency Motor:

PEWWE5-36-184T

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 8-Oct-2024

Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		3-PHASE INDUCTION MOTOR		259277 	
Model		Ser No.		Low Voltage 4-5-6 7-8-9 1-2-3 L1 L2 L3	
HP		S.F.		Rating	°C Amb Cont
Frame		P.F.		IP	Encl
Voltage	230/460	Hz		Code	Type
Amps		RPM		Ins Cl	Design
Nom.Eff.	FL	% 3/4	%	10:1 CT 20:1 VT PWM VFD	1.0SF
Class I DIV. 2 Groups A B C D		Amb.40°C	T3C(160°C)		
Class I Zone 2 IIC		Amb.55°C	T3A(180°C)	Date	
Grease type:		DE Brng ODE Brng			
WorldWide Electric Corporation					

Model	PEWWE5-36-184T						
HP	5	S.F.	1.25	IP	IP55	Encl	TEFC
Frame	184T	P.F.	0.88	Code	J	Type	
Voltage	230/460 V	Hz	60 Hz	Ins Cl	F	Ambient	40°C
Amps	12/6.01	RPM	3490	Design	B	DE Brng 6206ZZ C3 ODE Brng 6206ZZ C3	
Nom.Eff.	FL	88.5%	3/4	89.8%			
Class 1 Division 2 Groups A,B,C,D					T3C(160°C)		
					Grease type: -		

50Hz				
5 HP	200/400 V	14.3/7.1A	2885 rpm	85.8%